

# **ICNIRP** Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)<sup>1</sup>, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor<sup>2</sup> of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	17/07/2024	Time Survey completed:	13:17
Survey address:	Easingwold YO61		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY50672594	02/11/2023
Probe	Agos Aria-6000 Antenna	6000-1024	30/03/2021
Cabling	1.7m cable	1383	12/11/2023

<sup>&</sup>lt;sup>1</sup> https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

<sup>&</sup>lt;sup>2</sup> The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

### Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

## Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

<sup>\*</sup> This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. \*\* All other frequencies between 420 MHz and 6 GHz.

## Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Measurement time:	12:26
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00926
174-230 MHz	0.01074
470-694 MHz	0.00857
700 MHz	0.00335
800 MHz	0.00715
900 MHz	0.00059
1400 MHz	0.00080
1800 MHz	0.00237
1900 MHz	0.00019
2100 MHz	0.00123
2300 MHz	0.00045
2600 MHz TDD	0.00037
2600 MHz FDD	0.00019
3.4 GHz	0.00223
3.8 GHz	0.00493
Others	0.14286
Total	0.19529

Measurement time:	12:36
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00977
174-230 MHz	0.01163
470-694 MHz	0.00904
700 MHz	0.00207
800 MHz	0.00435
900 MHz	0.00061
1400 MHz	0.00276
1800 MHz	0.00544
1900 MHz	0.00021
2100 MHz	0.00273
2300 MHz	0.00048
2600 MHz TDD	0.00040
2600 MHz FDD	0.00021
3.4 GHz	0.00292
3.8 GHz	0.00537
Others	0.15356
Total	0.21154

Measurement time:	12:44
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01011
174-230 MHz	0.01196
470-694 MHz	0.00924
700 MHz	0.00148
800 MHz	0.00189
900 MHz	0.00062
1400 MHz	0.00350
1800 MHz	0.00880
1900 MHz	0.00021
2100 MHz	0.00386
2300 MHz	0.00049
2600 MHz TDD	0.00042
2600 MHz FDD	0.00022
3.4 GHz	0.00350
3.8 GHz	0.00562
Others	0.15972
Total	0.22165

Measurement time:	12:52
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01047
174-230 MHz	0.01237
470-694 MHz	0.00948
700 MHz	0.00162
800 MHz	0.00304
900 MHz	0.00064
1400 MHz	0.00472
1800 MHz	0.00396
1900 MHz	0.00022
2100 MHz	0.00116
2300 MHz	0.00051
2600 MHz TDD	0.00042
2600 MHz FDD	0.00022
3.4 GHz	0.00286
3.8 GHz	0.00579
Others	0.16474
Total	0.22223

Measurement time:	13:03
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01061
174-230 MHz	0.01251
470-694 MHz	0.00989
700 MHz	0.00240
800 MHz	0.00434
900 MHz	0.00066
1400 MHz	0.00167
1800 MHz	0.00247
1900 MHz	0.00022
2100 MHz	0.00113
2300 MHz	0.00051
2600 MHz TDD	0.00043
2600 MHz FDD	0.00023
3.4 GHz	0.00263
3.8 GHz	0.00591
Others	0.16756
Total	0.22319

Measurement time:	13:11
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01071
174-230 MHz	0.01259
470-694 MHz	0.00970
700 MHz	0.00146
800 MHz	0.00102
900 MHz	0.00065
1400 MHz	0.00096
1800 MHz	0.00120
1900 MHz	0.00022
2100 MHz	0.00104
2300 MHz	0.00052
2600 MHz TDD	0.00044
2600 MHz FDD	0.00023
3.4 GHz	0.00265
3.8 GHz	0.00592
Others	0.16795
Total	0.21727

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.